

Powerful Slimline Roller Door Opener for Residential Rolling Garage Doors

Rated door area	16.5m ²
Pulling force	550N
Motor	DC



Award Finalist for the 2009 Australian International Design Awards

Unique Features:

The MR850 provides new features including smooth product design and a smart status alarm output for connectivity to home security systems

Soft Start/Stop:

The MR850 is equipped with Chamberlain Soft Start/Stop technology. This is designed to ensure smooth and quiet door operation

Automatic Safety Function:

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop if obstructed going up. Your door can also be stopped and locked at any height for ventilation

Automatic Force Sensing:

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door

Three Channel Mini-Transmitter (two included):

A three channel mini transmitter with rolling code technology can control up to three different doors or gates

Wireless Wall Button (included):

Wireless push button equipped with rolling code technology for remote operation in the garage or home - designed to look like a conventional domestic switch

Manual Release:

In case of power failure you can simply activate the manual release to open your garage door

Accessories:

A wide range of wireless and other add-on accessories is available for this opener.

Warranty:

The MR850 comes with a two year general warranty and a five year warranty on the motor

Key Features	Optional Accessories	Specifications
<ul style="list-style-type: none"> Soft Start/Stop operation Auto safety function Auto force sensing Two 3 channel mini-transmitters Wireless wall button Rolling code technology with Peak Detect Up to 64 memory registers Ultra-bright LED lighting Manual release handle Minimum side room 45mm 5 year motor warranty 	<ul style="list-style-type: none"> IR Beams Motion-detecting control panel Keyed manual release Single channel transmitter 3 or 4 channel mini-transmitters Fingerprint keyless entry system Wireless keypad Evercharge™ standby power unit Automatic roller door locking system 	<ul style="list-style-type: none"> 24V DC motor with thermal overload protection Input voltage: 240V AC Rated door area 16.5m² Pulling force: 550N 433.92 MHz AM radio with rolling code Peak Detect receiver