

## “All-in-one Carton” Durable DC Sectional Door Opener

Rated door area	12.5m <sup>2</sup>
Pulling force	600N
Motor	DC
Drive	Chain



Suitable for sectional garage doors up to 12.5m<sup>2</sup>

**Soft Start/Stop Function:**

The MT60 is equipped with Chamberlain Soft Start/Stop technology, designed to ensure smooth and quiet door operation

**Automatic Safety Function:**

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop if obstructed going up. Your door can also be stopped and locked at any height for ventilation

**Automatic Force Sensing:**

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door

**Manual Release:**

In case of power failure you can simply activate the manual release to open your garage door

**Three Channel Mini Transmitter (two included):**

A three channel mini-transmitter with rolling code technology can control up to three different doors or gates

**Single Channel Transmitter (included):**

A single channel transmitter with rolling code technology, wall or car visor mountable

**All-in-one:**

The Merlin MT60 is supplied with motor and hardware in-one-box for easy handling and storage

**Warranty:**

The MT60 comes with a two year general warranty and a five year warranty on the motor

Key Features	Optional Accessories	Specifications
<ul style="list-style-type: none"> <li>• Auto safety function</li> <li>• Auto force sensing</li> <li>• Soft Start/Stop operation</li> <li>• Four piece C rail for enhanced strength and durability</li> <li>• Single channel transmitter</li> <li>• Two 3 channel mini-transmitters</li> <li>• Rolling code technology</li> <li>• Up to 12 memory registers</li> <li>• Manual release handle</li> <li>• Courtesy light</li> <li>• 5 year motor warranty</li> </ul>	<ul style="list-style-type: none"> <li>• 3 or 4 channel mini-transmitters</li> <li>• Wireless wall button CM128</li> <li>• Wireless keypad</li> <li>• IR beams</li> <li>• Keyed manual release</li> <li>• Motion detecting control panel</li> <li>• Add on receivers</li> <li>• Fingerprint keyless entry system</li> </ul>	<ul style="list-style-type: none"> <li>• 24V DC motor with thermal overload protection</li> <li>• Input voltage: 240V AC</li> <li>• Rated door area 12.5m<sup>2</sup></li> <li>• Pulling force: 600N</li> <li>• 433.92 MHz AM radio with rolling code</li> </ul>