

## Powerful DC Sectional Door Opener for Heavy Double Garage Doors

Rated door area	15m <sup>2</sup>
Pulling force	800N
Motor	DC
Drive	Chain/Belt



Suitable for all tilt or sectional garage doors up to 15m<sup>2</sup>

### Soft Start/Stop Function:

The MT800 is equipped with Chamberlain Soft Start/Stop technology, designed to ensure smooth and quiet door operation.

### Automatic Safety Function:

With its automatic safety function your garage door will stop and reverse automatically if obstructed going down or stop if obstructed going up. Your door can also be stopped and locked at any height for ventilation.

### Automatic Force Sensing:

Equipped with automatic force sensing, with each operation the garage door opener monitors and adjusts the force needed to open your garage door.

### Ultra Quiet Belt Option:

The C rail track combined with a belt drive system means the opener produces little or no sound when opening or closing.

### Wireless Wall Button (included):

Wireless push button equipped with rolling code technology for remote operation in the garage or home.

### Three Channel Mini Transmitter (two included):

A three channel mini-transmitter with rolling code technology can control up to three different doors or gates.

### Auto-close:

Automatically closes door after a pre-determined delay time. Requires IR Beams to be installed.

### 24V Accessory Output:

Allows easy installation of wired accessory devices directly to the opener's power supply terminals.

### Warranty:

The MT800 comes with a two year general warranty and a five year warranty on the motor.

Key Features	Optional Accessories	Specifications
<ul style="list-style-type: none"> <li>Soft Start/Stop operation</li> <li>Auto safety function</li> <li>Auto force sensing</li> <li>Chain or belt drive</li> <li>Two 3 channel mini-transmitters</li> <li>Wireless wall button</li> <li>Rolling code technology</li> <li>Up to 64 memory registers</li> <li>Manual release handle</li> <li>Courtesy light</li> <li>Auto close</li> <li>One piece or segmented C Rail</li> <li>24V accessory output</li> <li>5 year motor warranty</li> </ul>	<ul style="list-style-type: none"> <li>Safety beam sensors</li> <li>Motion detecting control panel</li> <li>Keyed manual release</li> <li>Single channel transmitter</li> <li>3 or 4 channel mini-transmitter</li> <li>Wireless wall button</li> <li>Wireless keypad</li> <li>Fingerprint keyless entry system</li> </ul>	<ul style="list-style-type: none"> <li>24 DC motor with thermal overload protection</li> <li>Input voltage: 240V AC</li> <li>Rated door area 15m<sup>2</sup></li> <li>Pulling force: 800N</li> <li>433.92 MHz AM radio with rolling code</li> </ul>